



**PARA LIGHT ELECTRONICS CO., LTD.**

11F., No. 8, Jiankang Rd., Zhonghe Dist., New Taipei City 235, Taiwan,

Tel: 886-2-2225-3733

Fax: 886-2-2225-4800

E-mail: [para@para.com.tw](mailto:para@para.com.tw)

<http://www.para.com.tw>

DATA SHEET

PART NO.: LC19F1RBWCT-CA-2.3A

REV: A / 2

CUSTOMER'S APPROVAL: \_\_\_\_\_

DCC: \_\_\_\_\_


DRAWING NO.: DS-77-22-0006G

DATE: 2023-2-21

Page

1

● PACKAGE OUTLINE DIMENSIONS



Notes:

1. a chip: Red; b chip: Blue; c chip: White
2. All dimensions are in millimeters.
3. Tolerance is  $\pm 0.1\text{mm}$  (.004") unless otherwise noted.

● Features

- \* Three color, top view, wide view angle Chip LED.
- \* Package in 8mm tape on 7" diameter reels.
- \* Compatible with automatic Pick & Place equipment.
- \* Compatible with Reflow soldering and Wave soldering processes.
- \* EIA STD package.
- \* I.C. compatible.
- \* Pb free product.
- \* Moisture sensitivity level: 3



# SURFACE MOUNT DEVICE LED

Part No.: LC19F1RBWCT-CA-2.3A

REV:A / 2

## ● Chip Materials

Chip	Light Color	Dice Material	Lens Color
a	R: Red	AllnGap	Water Clear
b	B: Blue	InGaN	
c	W: White	InGaN	

## ● Absolute Maximum Ratings (Ta=25°C)

SYMBOL	PARAMETER	Rating			UNIT
		R	W	B	
P <sub>D</sub>	Power Dissipation	60	80	80	mW
V <sub>R</sub>	Reverse Voltage	5			V
I <sub>F</sub>	Continuous Forward Current	25	25	25	mA
I <sub>PF</sub>	Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	80	80	80	mA
ESD	Electrostatic Discharge Threshold (HBM) <sup>Note A</sup>	/	1000	1000	V
T <sub>opr</sub>	Operating Temperature Range	-40 ~ +85			°C
T <sub>stg</sub>	Storage Temperature Range	-40 ~ +85			°C

NoteA:

HBM: Human Body Model. Seller gives no other assurances regarding the ability of to withstand ESD



# SURFACE MOUNT DEVICE LED

Part No.: LC19F1RBWCT-CA-2.3A

REV:A / 2

● Electro-Optical Characteristics(Ta=25°C, Condition B)

SYMBOL		PARAMETER	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
VF	R	Forward Voltage	IF = 2.3mA	1.6		2.2	V
	B			2.4		3.0	
	W			2.4		3.0	
IV	R	Luminous Intensity	IF = 2.3mA	11.2		45	mcd
	B			28		112	
	W			71		280	
$\lambda D$	R	Dominant Wavelength	IF = 2.3mA		620		nm
	B				470		
	/				/		
$\Delta\lambda$	R	Spectral Line Half-Width	IF = 2.3mA		17		nm
	B				15		
	W				25		
CIE(W)		X	IF = 2.3mA		0.295		
		Y			0.305		
$2\theta_{1/2}$		Half Intensity Angle	IF = 2.3 mA		130		deg

Notes:

1. Luminous intensity is measured with a light sensor and filter combination that proximates the CIE eye-response curve.
2.  $\theta_{1/2}$  is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
3. The dominant wavelength  $\lambda d$  is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.

● Red Typical Electro-Optical Characteristics Curves

(25°C Ambient Temperature Unless Otherwise Noted)




Fig.2 Forward Current vs. Forward Voltage




Fig.3 Luminous Intensity vs. Forward Current




Fig.4 Relative Luminous Intensity vs. Forward Current




Fig.5 Luminous Intensity vs. Ambient Temperature




Fig.6 Forward Current Derating Curve




Fig.7 Relative Intensity vs. Angle

● Blue Typical Electro-Optical Characteristics Curves

(25°C Ambient Temperature Unless Otherwise Noted)




Fig.2 Forward Current vs. Forward Voltage




Fig.3 Luminous Intensity vs. Forward Current




Fig.4 Relative Luminous Intensity vs. Forward Current




Fig.5 Luminous Intensity vs. Ambient Temperature




Fig.6 Forward Current Derating Curve




Fig.7 Relative Intensity vs. Angle

● White Typical Electro-Optical Characteristics Curves

(25°C Ambient Temperature Unless Otherwise Noted)




Fig.2 Forward Current vs.Forward Voltage




Fig.3 Luminous Intensity vs.Forward Current




Fig.4 Relative Luminous Intensity vs.Forward Current




Fig.5 Luminous Intensity vs.Ambient Temperature




Fig.6 Forward Current Derating Curve




Fig.7 Relative Intensity vs.Angle

● Label Explanation



ITEM CODE:PARA LIGHT

PART NO: LC19F1RBWCT-CA-2.3A

IV --- Luminous Intensity Code

LOT NO: EM S L 12 09 0110  
          A    B    C    D    E    F

A---EM: Emos Code

B---S:SMD

C---Local

D---Year

E---Month

F---SPEC.

PACKING QUANTITY OF BAG :

3000pcs for 150、170、110、155、115 series

4000pcs for 191 series

5000pcs for 192 series

DATE CODE: 2012 09 10  
                  G    H    I

G--- Year

H--- Month

I --- Day

● Typical Electro-Optical Characteristics Curves




Fig.1 Red Relative Intensity vs. Wavelength




Fig.1 White Relative Intensity vs. Wavelength





Fig.1 Blue Relative Intensity vs. Wavelength

● Reel Dimensions




Notes:

1. Taping Quantity: 3000pcs
2. The tolerances unless mentioned is  $\pm 0.1\text{mm}$ , Angle  $\pm 0.5^\circ$ , Unit: mm.

● Package Dimensions Of Tape And Reel

Polarity

Progressive direction




Notes: All dimensions are in millimeters.

● Cleaning


- \* If cleaning is required , use the following solutions for less than 1 minute and less than 40°C.
- \* Appropriate chemicals: Ethyl alcohol and isopropyl alcohol.
- \* Effect of ultrasonic cleaning on the LED resin body differs depending on such factors as the oscillator output, size of PCB and LED mounting method. The use of ultrasonic cleaning should be enforced at proper output after confirming there is no problem.

● Suggest Soldering Pad Dimensions




  
 Direction of PWB camber  
 and go to reflow furnace

● Suggest Sn/Pb IR Reflow Soldering Profile Condition:



● Suggest Pb-Free IR Reflow Soldering Profile Condition:





# SURFACE MOUNT DEVICE LED

Part No.: LC19F1RBWCT-CA-2.3A

REV:A / 2

● Bin Code List

Luminous Intensity (IV), Unit: mcd@2.3mA


Red			Blue			White		
Bin Code	Min	Max	Bin Code	Min	Max	Bin Code	Min	Max
L	11.2	18	N	28	45	Q	71	112
M	18	28	P	45	71	R	112	180
N	28	45	Q	71	112	S	180	280

Tolerance of each bin are  $\pm 15\%$

Color Rank (CIE chromaticity X , Y) @ 2.3mA									
W1					W2				
X	0.2855	0.2855	0.292	0.292	X	0.2855	0.2855	0.292	0.292
Y	0.297	0.3175	0.3245	0.304	Y	0.2795	0.297	0.304	0.2865
W3					W4				
X	0.292	0.292	0.2975	0.2975	X	0.292	0.2975	0.2975	0.292
Y	0.304	0.3245	0.331	0.3105	Y	0.304	0.3105	0.293	0.2865
W5					W6				
X	0.2975	0.2975	0.303	0.303	X	0.2975	0.303	0.303	0.2975
Y	0.3105	0.331	0.3375	0.317	Y	0.293	0.2995	0.317	0.3105

\* Measurement of Color coordinates :  $\pm 0.02$

C.I.E.Chromaticity Diagram



**● CAUTIONS****1.Application Limitation :**

The LED's described here are intended to be used for ordinary electronic equipment (such as office equipment, communication equipment and household application). Consult PARA's sales in advance for information on application in which exceptional quality and reliability are required, particularly when the failure or malfunction of the LED's may directly jeopardize life or health (such as airplanes, automobiles, traffic control equipment, life support system and safety devices).

**2.Storage :**

If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.

Baking treatment:  $60\pm 5^{\circ}\text{C}$  for 24 hours.

**3.Soldering**

Do not apply any stress to the lead frame during soldering while the LED is at high temperature.

Recommended soldering condition.

Reflow Soldering :

Pre-heat  $120\sim 150^{\circ}\text{C}$ , 120sec. MAX., Peak temperature :  $240^{\circ}\text{C}$  Max. Soldering time : 10 sec Max.

Soldering Iron : (Not recommended)

Temperature  $300^{\circ}\text{C}$  Max., Soldering time : 3 sec. Max.(one time only), power dissipation of iron : 20W Max. use SN60 solder of solder with silver content and don't to touch LED lens when soldering.

Wave soldering :

Pre-heat  $100^{\circ}\text{C}$  Max, Pre-heat time 60 sec. Max, Solder wave  $260^{\circ}\text{C}$  Max, Soldering time 5 sec. Max. preformed consecutively cooling process is required between 1<sup>st</sup> and 2<sup>nd</sup> soldering processes.

4. Lead-Free Soldering

For Reflow Soldering :

- 1、 Pre-Heat Temp:150-180°C,120sec.Max.
- 2、 Soldering Temp:Temperature Of Soldering Pot Over 230°C,40sec.Max.
- 3、 Peak Temperature:260°C , 5sec.
- 4、 Reflow Repetition:2 Times Max.
- 5、 Suggest Solder Paste Formula 93.3 Sn/3.1 Ag/3.1 Bi /0.5 Cu

For Soldering Iron (Not Recommended) :

- 1、 Iron Tip Temp:350°C Max.
- 2、 Soldering Iron:30w Max.
- 3、 Soldering Time:3 Sec. Max. One Time.


For Dip Soldering :

- 1、 Pre-Heat Temp:150°C Max. 120 Sec. Max.
- 2、 Bath Temp:265°C Max.
- 3、 Dip Time:5 Sec. Max.

5. Drive Method

Circuit model A

Circuit model B



(A)Recommended circuit.

(B)The difference of brightness between LED's could be found due to the Vf-If characteristics of LED.