



PARA LIGHT ELECTRONICS CO., LTD.

11F., No. 8, Jiankang Rd., Zhonghe Dist., New Taipei City 235, Taiwan,

Tel: 886-2-2225-3733

Fax: 886-2-2225-4800

E-mail: para@para.com.tw

<http://www.para.com.tw>

DATA SHEET

PART NO.: L-C19F1RGBCT-CA

REV: A / 5


CUSTOMER'S APPROVAL: _____

DCC: _____

DRAWING NO.: DS-79-15-0001

DATE: 2021-12-3 Page 1

● PACKAGE OUTLINE DIMENSIONS



Notes:

1. a chip: Red; b chip: Green; c chip: Blue
2. All dimensions are in millimeters.
3. Tolerance is $\pm 0.1\text{mm}$ (.004") unless otherwise noted.

● Features

- * Three color, top view, wide view angle Chip LED.
- * Package in 8mm tape on 7" diameter reels.
- * Compatible with automatic Pick & Place equipment.
- * Compatible with Reflow soldering and Wave soldering processes.
- * EIA STD package.
- * I.C. compatible.
- * Pb free product.
- * Moisture sensitivity level: 3



SURFACE MOUNT DEVICE LED

Part No.: L-C19F1RGBCT-CA

REV:A / 5

● Chip Materials

| Chip | Light Color | Dice Material | Lens Color |
|------|-------------|---------------|-------------|
| a | R: Red | AlInGap | Water Clear |
| b | G: Green | InGaN | |
| C | B: Blue | InGaN | |

● Absolute Maximum Ratings (Ta=25°C)

| SYMBOL | PARAMETER | Rating | | | UNIT |
|------------------|---|-----------|------|------|------|
| | | R | G | B | |
| P _D | Power Dissipation | 75 | 100 | 100 | mW |
| V _R | Reverse Voltage | 5 | | | V |
| I _F | Continuous Forward Current | 25 | 25 | 25 | mA |
| I _{PF} | Peak Forward Current | 80 | 100 | 100 | mA |
| ESD | Electrostatic Discharge Threshold (HBM) ^{Note A} | 2000 | 1000 | 1000 | V |
| T _{opr} | Operating Temperature Range | -40 ~ +85 | | | °C |
| T _{stg} | Storage Temperature Range | -40 ~ +85 | | | °C |

Note A:

HBM: Human Body Model. Seller gives no other assurances regarding the ability of to withstand ESD

● Electro-Optical Characteristics (Ta=25°C)

| SYMBOL | | PARAMETER | TEST | MIN. | TYP. | MAX. | UNIT |
|--------|---|--------------------------|-----------|------|------|------|------|
| VF | R | Forward Voltage | IF = 20mA | 1.5 | 1.9 | 2.4 | V |
| | G | | | 2.8 | 3.1 | 3.5 | |
| | B | | | 2.8 | 3.0 | 3.4 | |
| IV | R | Luminous Intensity | IF = 20mA | 71 | 112 | 180 | mcd |
| | G | | | 280 | 450 | 710 | |
| | B | | | 71 | 112 | 180 | |
| λD | R | Dominant Wavelength | IF = 20mA | 618 | 623 | 628 | nm |
| | G | | | 520 | 525 | 530 | |
| | B | | | 465 | 470 | 475 | |
| Δλ | R | Spectral Line Half-Width | IF = 20mA | | 17 | | nm |
| | G | | | | 15 | | |
| | B | | | | 25 | | |
| 2θ1/2 | | Half Intensity Angle | IF = 20mA | | 130 | | deg |
| IR | R | Reverse Current | VR = 5V | | | 10 | μA |
| | G | | | | | 50 | |
| | B | | | | | 50 | |

Notes:

- Luminous intensity is measured with a light sensor and filter combination that proximities the CIE eye-response curve.
- $\theta 1/2$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- The dominant wavelength λd is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.
- Caution in ESD :
Static Electricity and surge damages the LED. It is recommended use a wrist band or anti-electrostatic glove when handling the LED. All devices, equipment and machinery must be properly grounded.
- Major standard testing equipment by “Instrument System” Model : CAS140B Compact Array Spectrometer and “KEITHLEY” Source Meter Model : 2400.

● Red Typical Electro-Optical Characteristics Curves

(25°C Ambient Temperature Unless Otherwise Noted)




Fig.2 Forward Current vs. Forward Voltage




Fig.3 Luminous Intensity vs. Forward Current




Fig.4 Relative Luminous Intensity vs. Forward Current




Fig.5 Luminous Intensity vs. Ambient Temperature




Fig.6 Forward Current Derating Curve




Fig.7 Relative Intensity vs. Angle

● **Green Typical Electro-Optical Characteristics Curves**

(25°C Ambient Temperature Unless Otherwise Noted)




Fig.2 Forward Current vs.Forward Voltage




Fig.3 Luminous Intensity vs.Forward Current




Fig.4 Relative Luminous Intensity vs.Forward Current




Fig.5 Luminous Intensity vs.Ambient Temperature




Fig.6 Forward Current Derating Curve




Fig.7 Relative Intensity vs.Angle

● **Blue Typical Electro-Optical Characteristics Curves**

(25°C Ambient Temperature Unless Otherwise Noted)




Fig.2 Forward Current vs.Forward Voltage




Fig.3 Luminous Intensity vs.Forward Current




Fig.4 Relative Luminous Intensity vs.Forward Current




Fig.5 Luminous Intensity vs.Ambient Temperature




Fig.6 Forward Current Derating Curve




Fig.7 Relative Intensity vs.Angle

● Label Explanation



ITEM CODE:PARA LIGHT

PART NO: L-C19F1RGBCT-CA

IV --- Luminous Intensity Code

LOT NO: EM S L 12 09 0110
 A B C D E F

A---EM: Emos Code

B---S:SMD

C---Local

D---Year

E---Month

F---SPEC.

PACKING QUANTITY OF BAG :

3000pcs for 150、170、110、155、115 series

4000pcs for 191 series

5000pcs for 192 series

DATE CODE: 2012 09 10
 G H I

G--- Year

H--- Month

I --- Day

● Typical Electro-Optical Characteristics Curves




Fig.1 Red Relative Intensity vs. Wavelength




Fig.1 Green Relative Intensity vs. Wavelength





Fig.1 Blue Relative Intensity vs. Wavelength


● Reel Dimensions



Notes:

1. Taping Quantity: 3000pcs
2. The tolerances unless mentioned is $\pm 0.1\text{mm}$, Angle $\pm 0.5^\circ$, Unit: mm.


● Package Dimensions Of Tape And Reel



Notes: All dimensions are in millimeters.


● Cleaning

- * If cleaning is required , use the following solutions for less than 1 minute and less than 40°C.
- * Appropriate chemicals: Ethyl alcohol and isopropyl alcohol.
- * Effect of ultrasonic cleaning on the LED resin body differs depending on such factors as the oscillator output, size of PCB and LED mounting method. The use of ultrasonic cleaning should be enforced at proper output after confirming there is no problem.


● Suggest Soldering Pad Dimensions

Direction of PWB camber
and go to reflow furnace

● Suggest Sn/Pb IR Reflow Soldering Profile Condition:



● Suggest Pb-Free IR Reflow Soldering Profile Condition:





SURFACE MOUNT DEVICE LED

Part No.: L-C19F1RGBCT-CA

REV:A / 5

● Bin Code List

Luminous Intensity (IV), Unit: mcd@20mA

| Red (a chip) | | | Green (b chip) | | | Blue (c chip) | | |
|--------------|-----|-----|----------------|-----|-----|---------------|-----|-----|
| Bin Code | Min | Max | Bin Code | Min | Max | Bin Code | Min | Max |
| Q | 71 | 112 | T | 280 | 450 | Q | 71 | 112 |
| R | 112 | 180 | U | 450 | 710 | R | 112 | 180 |

Tolerance of each bin are $\pm 15\%$

Dominant Wavelength (Hue), Unit: nm@20mA

| Green (b chip) | | | Blue (c chip) | | |
|----------------|-----|-----|---------------|-----|-----|
| Bin Code | Min | Max | Bin Code | Min | Max |
| AP | 520 | 525 | AC | 465 | 470 |
| AQ | 525 | 530 | AD | 470 | 475 |

Tolerance of each bin are $\pm 1\text{nm}$

CAUTIONS

1.Application Limitation:

The LED's described here are intended to be used for ordinary electronic equipment (such as office equipment, communication equipment and household application). Consult PARA's sales in advance for information on application in which exceptional quality and reliability are required, particularly when the failure or malfunction of the LED's may directly jeopardize life or health (such as airplanes, automobiles, traffic control equipment, life support system and safety devices).

2.Storage:

If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.

Baking treatment: $60\pm 5^{\circ}\text{C}$ for 24 hours

3.Soldering

Do not apply any stress to the lead frame during soldering while the LED is at high temperature.

Recommended soldering condition.

Reflow Soldering:

Pre-heat 120~150 °C, 120sec. MAX., Peak temperature : 240 °C Max. Soldering time: 10 sec Max.

Soldering Iron: (Not recommended)

Temperature 300 °C Max., Soldering time : 3 sec. Max.(one time only), power dissipation of iron : 20W Max. use SN60 solder of solder with silver content and don't to touch LED lens when soldering.

Wave soldering:

Pre-heat 100 °C Max, Pre-heat time 60 sec. Max, Solder wave 260 °C Max, Soldering time 5 sec. Max. performed consecutively cooling process is required between 1st and 2nd soldering processes.

4. Lead-Free Soldering

For Reflow Soldering:

- 1、 Pre-Heat Temp:150-180°C,120sec.Max.
- 2、 Soldering Temp: Temperature Of Soldering Pot Over 230°C,40sec.Max.
- 3、 Peak Temperature:260°C , 5sec.
- 4、 Reflow Repetition:2 Times Max.
- 5、 Suggest Solder Paste Formula 93.3 Sn/3.1 Ag/3.1 Bi /0.5 Cu


For Soldering Iron (Not Recommended):

- 1、 Iron Tip Temp:350°C Max.
- 2、 Soldering Iron:30w Max.
- 3、 Soldering Time:3 Sec. Max. One Time.

For Dip Soldering:

- 1、 Pre-Heat Temp:150°C Max. 120 Sec. Max.
- 2、 Bath Temp:265°C Max.
- 3、 Dip Time:5 Sec. Max.

5. Drive Method



(A)Recommended circuit.

(B)The difference of brightness between LED`s could be found due to the Vf-If characteristics of LED.